

X EXTREME VR1



PRODUCT PREVIEW

All-round, road legal, semi-slick tyre with directional open tread pattern. Type-W3A and W5 versions are **designed for rally use in overcast and rainy conditions**. These products are distinguished by reinforced sidewalls and high performance rubber compounds which guarantees the highest level of grip. The Type-V2, Type-S3 and Type-S4 versions are designed for drifting. **Regular wear and stable grip till the end are the biggest advantages over competition.**

TECHNICAL SPECIFICATION

TABLE 1: DIMENSIONS

Tyre Size	Load/Speed Index	Recommended rim width [inch]	Approx. Weight** [kg]	Tread Depth [mm]	Overall Diameter [mm]	Tread Width [mm]
195/50 R15	82 H	6.5/7.0	9.0/7.1	6.5	577	200
205/45 R16	83 H/V*	7.0/7.5	9.0/8.4	6.5	590	200
205/45 R17	84 H/V*	7.0/7.5	10.0	6.5	615	200
225/45 R17	91 H/V*	8.0/8.5	12.0/10.5	6.5	632	220
245/40 R17	91 H/V*	8.5/9.0/9.5	12.5/11.0	6.5	625	240
245/40 R18	93 H/V*	8.5/9.0/9.5	13.0/11.5	6.5	650	240
255/35 R18	90 H/V*	9.0/9.5/10.0	13.0/12.0	7.5	634	260
265/35 R18	93 H/W*	9.5/10.0/10.5	13.0/12.0	7.5	646	265

* - H index applies to Type-W compounds

** - Type-W / Type-S&V

TABLE 2: RUBBER COMPOUNDS

Version	Hardness	Application	Compound Operating Temperature [°C]	Treadwear Indication
TYPE - W3A	SUPER SOFT	RALLY (WET)	0 - 30	50
TYPE - W5	SOFT	RALLY (DAMP / WET)	20 - 40	80
TYPE - V2	MEDIUM	DRIFT (REGULAR GRIP)	40 - 80	240
TYPE - S3	MEDIUM	DRIFT (HIGH GRIP)	40 - 120	220
TYPE - S4	SOFT	DRIFT (ULTIMATE GRIP)	30 - 80	160
TYPE - X	HARD	DRIFT (LONG LIFE)	-	500