



# X EXTREME VR2

A modern competition road legal semi-slick tyre with asymmetric tread and shoulder design. The outside structure of this tyre increases the grip and precision while cornering, whereas the inside structure provides maximum road contact on the straight line. Together with reinforced sidewalls and advanced compounds the VR2 offers supreme grip and immediate steering response.

## PRODUCT PREVIEW

## TECHNICAL SPECIFICATION

**TABLE 1: DIMENSIONS**

\* - H index applies to Type-W compounds \*\* - Type-R&W / Type-S

Tyre Size	Load/Speed Index	Recommended rim width [inch]	Approx. Weight** [kg]	Tread Depth [mm]	Overall Diameter [mm]	Tread Width [mm]
185/60 R13	80 H	6.0/6.5	8.3	5.0	548	185
205/60 R13	86 H	6.5/7.0	9.5	5.0	570	190
175/50 R13	72 H	6.0/6.5	6.5	5.0	501	175
185/55 R14	80 H	6.0/6.5	7.8	5.0	552	185
195/55 R15	85 H	6.5/7.0	9.1	5.0	590	185
195/50 R15	82 H	6.5/7.0	8.7	5.0	574	195
205/55 R16	91 H	6.5/7.0	10	5.0	625	195
195/50 R16	88 H	6.5/7.0	9	5.0	595	190
205/50 R16	87 H	7.0/7.5	9.8	5.0	605	204
205/45 R17	84 H/V*	7.0/7.5	9.3	5.0	609	200
215/45 R17	87 V	7.5/8.0	10.5	5.0	625	207
225/45 R17	91 H/V*	8.0/8.5	11.5/10.5	5.0	630	218
245/40 R17	91 V	9.0/9.5	11.1	5.0	625	240
225/40 R18	88 H/V*	8.0/8.5	11.5/10.5	5.0	635	230
235/40 R18	91 V	8.5/9.0	11.5	5.0	639	240
255/35 R18	90 H/W*	9.0/9.5	12.0	5.0	631	255
265/35 R18	93 H/W*	9.5/10.0	12.5/12.0	5.0	633	260
285/35 R18	97V	10.5/11.0/11.5	14	5.0	665	270
235/35 R19	91 V	8.5/9.0	10.8	5.0	641	240

**TABLE 2: RUBBER COMPOUNDS**

Version	Hardness	Application	Compound Operating Temperature [°C]	Treadwear Indication
TYPE - W3A	SUPER SOFT	DRY/DAMP SURFACE	0 - 30	50
TYPE - R5A	SOFT	DRY/DAMP SURFACE	15 - 50	80
TYPE - R7A	MEDIUM	DRY SURFACE	30 - 80	140
TYPE - R9A	HARD	DRY SURFACE	50 - 110	200
TYPE - N	HARD	TRACKDAY	30 - 90	220
TYPE - HL	MEDIUM	HOT-LAP / TIME ATTACK	40-70	50